

## video cable SC-Monomax 0.41/1.9 CPR- Version; 1 x 0,41; PVC Ø 3,60 mm; black; Eca Art. No.: 600-0041C

ANALOG

DIGITAL

OFC



### General Data

Article number :	600-0041C
Name :	SC-Monomax 0.41/1.9 CPR-Version
EAN :	4049371377904
Properties :	Digital 75 Ω
Properties :	Analog
Application area :	Installation
Application area :	Studio / Broadcast
Application :	video cable
Colour :	black
Colour detailed :	black
Old article number :	600-0041
BPVo-Euroclass :	Eca

### Technical Data

Jacket material :	PVC
Jacket Ø [mm] :	3,60
Number of Channels (video) :	1
Inner conductor Ø (video) [mm] :	0,41
AWG (video) :	26
Shielding :	Copper braiding tin-plated + AL / PT foil
Copper strands (video) :	1
Copper strand Ø (video) [mm] :	0,41
Conductor insulation Ø [mm] :	1,90
Weight per 1 m [g] :	14.18
UV-resistant :	yes
Fire load per m [kWh] :	0,06
Style variant :	round
Packing :	100 m spool
Velocity factor :	0,85
Width [mm] :	3,6
Height [mm] :	3,6

### Electrical Data

Capacity wire/electic screen at 1m (video) [pF] :	53
Damping at 50 MHz (100m & 20° C) [dB] :	11,4
Damping at 200 MHz (100m & 20° C) [dB] :	22,1
Damping at 470 MHz (100m & 20° C) [dB] :	32,9
Damping at 862 MHz (100m & 20° C) [dB] :	44,8
Damping at 1000 MHz (100m & 20° C) [dB] :	48,8
Damping at 1485 MHz (100m & 20° C) [dB] :	58,9
Damping at 1750 MHz (100m & 20° C) [dB] :	63,5
Damping at 2150 MHz (100m & 20° C) [dB] :	69,6

Damping at 3000 MHz (100m &amp; 20° C) [dB] : 84,7

Impedance [Ω] : 75

Conductor resistance per 1 km [Ω] : 320

Shield. resistance per 1 km [Ω] : 26