

## RG59 & Phono SC-AQUA MARINEX VIDEO 0.6L/3.7; 1 x 0,60/3,30; PUR-SR Ø 6,40 mm; black

Art. No.: **600-0241AQ**



### General Data

|                    |                                   |
|--------------------|-----------------------------------|
| Article number :   | 600-0241AQ                        |
| Name :             | SC-AQUA MARINEX VIDEO<br>0.6L/3.7 |
| EAN :              | 4049371194464                     |
| Properties :       | Analog                            |
| Properties :       | Halogen-free / LSZH               |
| Properties :       | PUR                               |
| Properties :       | Digital 75 Ω                      |
| Properties :       | Underwater / submerged            |
| Application area : | Stage / live                      |
| Application area : | Mobile outdoor / indoor           |
| Application area : | Installation                      |
| Application area : | ELA 100 V                         |
| Application :      | RG59 & Phono                      |
| Colour :           | black                             |
| Colour detailed :  | black                             |
| BPVo-Euroclass :   | Fca                               |

### Electrical Data

|   |      |
|---|------|
| Capacity wire/electic screen at 1m (video) [pF] : | 70   |
| Impedance [Ω] :                                   | 75   |
| Conductor resistance per 1 km [Ω] :               | 89   |
| Conductor resistance per 1 km (video) [Ω] :       | 89   |
| Shield. resistance per 1 km [Ω] :                 | 12,5 |

### Technical Data

|  |   |
|--|---|
| Jacket material :                            | PUR-SR  |
| Jacket Ø [mm] :                              | 6,40  |
| Number of Channels (video) :                 | 1   |
| Inner conductor (video) :                    | 1   |
| Inner conductor (video) [mm <sup>2</sup> ] : | 0,22  |
| Inner conductor Ø (video) [mm] :             | 0,60  |
| AWG (video) :                                | 23  |
| Shielding :                                  | Copper braiding + special<br>protective banding |
| Shielding factor [%] :                       | 90  |
| Copper strands (video) :                     | 7   |
| Copper strand Ø (video) [mm] :               | 0,20  |
| Conductor insulation material :              | PO  |
| Conductor insulation Ø [mm] :                | 3,30  |
| Conductor insulation Ø (video) [mm] :        | 3,30  |
| Weight per 1 m [g] :                         | 51  |
| UV-resistant :                               | yes   |
| Fire load per m [kWh] :                      | 0,3   |
| Style variant :                              | round   |
| Packing :                                    | bulk stock                                      |
| Velocity factor :                            | 0,66  |
| Temperature min. [°C] :                      | -40   |
| Temperature max. [°C] :                      | 80  |
| Width [mm] :                                 | 6,4   |
| Height [mm] :                                | 6,4   |