

HYPER-PRO TOP 12A

12" 1200W Peak 2-way Powered Loudspeakers with Easy Control DSP

HYPER-PRO TOP Series speakers are part of a wider range of SOUNDSATION Pro Audio product line, of which they represent the cutting edge. 1200W peak power, selected transducers, powerful DSP, advanced housing material and anti-scratch black paint: all ingredients wisely combined to offer the best to even the most demanding professionals. HYPER-PRO series 12" and 15" woofers sound punchy and loud; the 1.35" driver lets them sound crystal clear. With the Easy Control DSP, you take total control of your sound. Press and rotate the control knob - that's all. The graphic backlit display shows what you want to select. Choose from 4 sound programs, edit the sound character and simply get. With the separately controllable inputs, you decide whether want to connect a microphone, a mixer, an instrument or a player. And this twice. On both input channels, you can choose if you want to connect a cable with XLR or 6.3mm jack connectors. Choose the "MIC" or "LINE" mode and set the input levels quickly with the gain controls, independently from each other.



€ 486,00

including VAT



KEY FEATURES

Bi-Amped Active Speaker

1200W Peak Power

Amplifier Class-D (low-frequencies); Class-AB (high-frequencies)

3-Band EQ

4-Preset DSP (Music, Live, Speech, DJ)

Graphic back-lit display

Sturdy and Lightweight Polypropylene Enclosure with black anti-scratch paint

Standard D36mm tripod / pole hole

30° and 45° Stage Monitor Use Angles

MORE SPECIFICATIONS

Frequency Response	52Hz - 20kHz / -10dB
Max SPL	124 dB
Low-freq. Transducer	12" Woofer
High-freq. Transducer	1.35" Compression Driver
Coverage	90° x 60°
Low-Frequency Amplifier	Class-D 300W RMS - 1000W Picco
High-Frequency Amplifier	Class-AB 50W RMS - 200W Picco
AC Mains	220/240V - 50/60Hz
Power Consumption	365W
Fuse	T3.15A-250V
3-Band EQ	High (10kHz, ±12dB), Mid (2kHz, ±12dB), Low (100Hz, ±12dB)
Presets	Music, Live, Speech, DJ
High-Pass Filter Cut	80Hz / 100Hz / 120Hz / 150Hz
Digital Master Level	-60dB / + 10dB (70 steps)
Input Connections	2 x COMBO (XLR + 1/4" Jack, balanced)
Output Connections	1 x XLR (Mix output, balanced)
Housing material	Polypropylene
1.2mm Steel Grille	
Handles	2 on sides; 1 on top
Tripod/Pole Hole	Standard D36mm
Stage Monitor Use Angle	30° and 45°
Speaker Size (WxHxD)	413 x 677 x 410 mm
Packing Size (WxHxD)	430 x 690 x 430 mm
Speaker Weight	14.7 kg
Carton Weight	17.8 kg