



## ArtGate DIN

**Bidirectional DMX<->ArtNet/sACN converter, splitter, booster, intelligent merger**

DIN mounted multifunctional converters that translate Ethernet protocols (ArtNet, sACN) into DMX to control more lighting fixtures through single Ethernet LAN 10/100Base-T link. Trigger inputs provide ability to launch pre-programmed DMX scenarios when triggers (e.g. fire alarm) are activated even if the console is down. Two RJ-45 Ethernet inputs and pluggable 15EDGVC terminal blocks for seamless connection. Up to 8 DMX outputs per one device, second Ethernet port adds cascading availability through integrated switch. May be powered through Ethernet (PoE) without power cabling.



### Advantages

- Support PoE
- Minimum loading time, fastest recovery after short power failure
- Master IP that never gets lost
- Alarm triggered pre-programmed scenarios
- Full protection from dust and smoke increases product lifetime
- Maximum surge protection from 100 to 315 V
- Full galvanic isolation of all ports
- Simple user-friendly web interface
- Configurable DMX port direction

### Merging Options

- HTP: highest takes precedence
- LTP: latest takes precedence
- AUTO: last modified takes precedence – intelligent merging mode that provides availability to manage installation from two consoles simultaneously
- OVERLAY: merges custom slots from two ArtNet/sACN streams, fully customized through web interface
- PRIORITY: for sACN streams with priority tag, console with the highest priority for a given Universe will be in charge



DMX Bi-Direct



2 IP addresses per Device



User-Friendly Web Interface



Supports RDM



UltraStart



Galvanically Isolated Ports



Natural Heat Convection



Permanent Laser Engraving



Power over Ethernet



Trigger Input

### Application

- Convert DMX512 into ArtNet and sACN protocols in both directions to transmit DMX data through Ethernet LAN
- Transmit more DMX streams with less cables
- Lighting control and management through single Ethernet network
- Convert mapped video content from mapping software into DMX streams
- Ensure interfacing between modern stage lighting software and DMX lighting
- Real-time control of video projectors and laser units supporting ArtNet or sACN from DMX console

# ArtGate DIN

Bidirectional DMX<->ArtNet/sACN converter,  
splitter, booster, intelligent merger

Version: 3.00  
15 nov 2019

## Technical Specifications

### Mechanical

**Housing:** DIN mounted case (12 modules)

**Material:** metal, plastic

**Dimensions, mm:** 210(D) x 105(H) x 75(W)

**Mass:** 0.85 kg

**Mounting:** power cabinet

### Power & Electrical

**Power supply:** ~90-250 VAC, 50/60 Hz, PoE (optional)

**Input Power (max):** 5 W

**Mains Fuse:** 0.5 A

### Environmental

**Operating Temperature:** -40...+70°C

**Storage Temperature:** -50...+80°C

**Operating Relative Humidity (max):** 95%

**IP Rating:** IP 20

**Certification:** CE, RoHS

**Warranty:** 36 month (Return to base)

### Control / Data Connections

**Supported protocols:** ArtNet I, II, III, IV/ sACN,  
DMX512, RDM

**DMX refresh rate:** 44 Hz

### Inputs / Outputs

**DMX ports:** 4 or 8 isolated

**DMX connectors:** terminal blocks 15 EDGVC

**Ethernet ports:** 2 (10/100 Base-TX)

**Ethernet connectors:** 2x RJ-45

**Trigger inputs:** 2

### Configuration / Indication

**Setup:** web-interface

**Indication:** LEDs for DMX and Ethernet activity

### Package Contents

ArtGate DIN

Connectors kit

## Product Line

Name	Modification	Product code
ArtGate DIN	4 DMX inputs/outputs, 2 Ethernet ports, PoE	AGD-1-4D2E
	8 DMX inputs/outputs, 2 Ethernet ports, PoE	AGD-1-8D2E



+ 44 (0) 208 991 33 19  
office@sundrax.com  
www.sundrax.com

# ArtGate DIN

Bidirectional DMX<->ArtNet/sACN converter,  
splitter, booster, intelligent merger

Version: 3.00  
15 nov 2019

## Connection Scheme

