



PowerGate Arma

Waterproof DMX/ArtNet/sACN over Powerline transceiver

DMX transceivers employing existing powerlines (110V/220V) to transmit DMX signal using PWRDMX technology introduced by Sundrax in 2007. Perfect solution if new cabling or wireless transmission is hindered or impossible e.g. conversion to DMX lighting for historic facades, architectural monuments, landmarks, in-ground lighting.

Powergates support ArtNet and sACN input through single Ethernet LAN 10/100Base-T link and have up to 4 DMX outputs. DMX ports are configurable through web-based management page. All PowerGates may be configured as transmitters or receivers. Tough and compact waterproof metal enclosure (IP65) specifically crafted for outdoor use.



Advantages

Use existing powerlines to transmit DMX streams

Ethernet port for web configuration and ArtNet/sACN data transmission

Minimum loading time, fastest recovery after short power failure

Full protection from dust and smoke increases product lifetime

Full galvanic isolation of all ports

Simple user-friendly web interface

High resistance to interference (IP65)

Maximum surge protection (100-315 V)



DMX Bi-Direct




Supports RDM



UltraStart



Galvanically Isolated Ports



Natural Heat Convection



Highest Ingress Protection

Advantages

HTP: highest takes precedence

LTP: latest takes precedence

AUTO: last modified takes precedence – intelligent merging mode that provides availability to manage installation from two consoles simultaneously

OVERLAY: merges custom slots from two ArtNet/sACN streams, fully customized through web interface

PRIORITY: for sACN streams with priority tag, console with the highest priority for a given Universe will be in charge

Application

Control DMX lights through existing powerline when new cabling or wireless transmission is hindered or impossible

DMX/ArtNet/sACN transmission between indoor spaces when new cabling is impossible

Outdoor installations when new cabling or wireless transmission is hindered or impossible

Convert lighting of facades, architectural monuments, landmarks, or historic buildings to DMX when new cabling is impossible

Convert in-ground lighting to DMX fixtures without new cabling

PowerGate Arma

Waterproof DMX/ArtNet/sACN over Powerline transceiver

Version: 4.01
19 Aug 2019

Technical Specifications

Mechanical

Housing: solid case

Material: metal

Dimensions, mm: 171(D) x 55(H) x 121(W)

Mass: 0.85 kg

Mounting: Surface, Truss

Power & Electrical

Power supply: ~90-270 VAC, 50/60 Hz

Input Power (max): 5 W

Mains Fuse: 0.1 A

Environmental

Operating Temperature: -40...+70°C

Storage Temperature: -50...+80°C

Operating Relative Humidity (max): 100%

IP Rating: IP65

Certification: CE, RoHS

Warranty: 36 Month (Return to base)

Control / Data Connections

Supported protocols: DMX512, RDM, PWR DMX

DMX data refresh rate: 44 Hz

Ethernet connectors: LSA-PLUS® connector

Inputs / Outputs

DMX ports: 1 or 4 isolated

DMX connectors: Terminal blocks 15EDGVC

Ethernet port: 1 (10/100 Base-TX)

Ethernet connector: LSA-PLUS® connector

Configuration / Indication

Setup: web-interface

Indication: LEDs for DMX activity

Package Contents

PowerGate Arma

Product Line


Name	Modification	Product code
PowerGate Arma	1 DMX input/output, Ethernet, AC 4 DMX inputs/outputs, Ethernet, AC	PGA-0-DE PGA-0-4DE

PowerGate Arma

Waterproof DMX/ArtNet/sACN over Powerline transceiver

Version: 4.01
19 Aug 2019

Connection Scheme



Accessories

Name

Truss mounting kit (Solid, Arma)
Surface mounting kit (Solid, Arma)

Product code

DMX-MCA-1-120
DMX-MCA-2-120