



The CBR10 is the most compact model in its series. While delivering astonishing power for its size and weight, the CBR10 is ideal for both portable and installed applications.

---

**Specifications**

General specifications		
Speaker type		2-way Speaker, Bass-reflex Type
Frequency range (-10dB)		50 Hz - 20 kHz
Nominal coverage	H	90°
	V	60°
Components	LF	10" Cone, 2" Voice Coil (Ferrite Magnet)
	HF	1" Voice Coil, Compression Driver (Ferrite Magnet)
Power rating	NOISE	175W
	PGM	350W
	PEAK	700W
Nominal impedance		8Ω
SPL	Sensitivity (1W; 1m on axis)	94dB SPL
	Peak (Calculated)	123 dB SPL
I/O connectors		1/4" Phone x 1, speakON NL4MP x 1
Dimensions	W	308mm (12.1")
	H	493mm (19.4")
	D	289mm (11.4")
Net weight		9.4 kg (20.7 lbs)
Cabinet material		Plastic
Finish		Black
Handle		Top x 1
Flying and mounting hardware		Bottom x 2, Rear x 1 (Fit for M8 x 15mm Eyebolts)
Pole socket		Φ35 mm Bottom x 1
Accessories		Optional Speaker Bracket: BBS251, BCS251, BWS251-300, BWS251-400
Crossover		2.8 kHz