



The CBR12 represents a perfect balance of size and performance. Ideal for front-of-house, floor monitoring or even rigged applications, the CBR12 is an ideal choice for a wide range of applications.

---

**Specifications**

General specifications		
Speaker type		2-way Speaker, Bass-reflex Type
Frequency range (-10dB)		48 Hz - 20 kHz
Nominal coverage	H	90°
	V	60°
Components	LF	12" Cone, 2" Voice Coil (Ferrite Magnet)
	HF	1.4" Voice Coil, Compression Driver (Ferrite Magnet)
Power rating	NOISE	175W
	PGM	350W
	PEAK	700W
Nominal impedance		8Ω
SPL	Sensitivity (1W; 1m on axis)	96dB SPL
	Peak (Calculated)	125 dB SPL
I/O connectors		1/4" Phone x 1, speakON NL4MP x 1
Dimensions	W	376mm (14.8")
	H	601mm (23.7")
	D	348mm (13.7")
Net weight		13.9 kg (30.6 lbs)
Cabinet material		Plastic
Finish		Black
Handle		Side x 2
Flying and mounting hardware		Bottom x 2, Rear x 1 (Fit for M8 x 15mm Eyebolts)
Pole socket		Φ35 mm Bottom x 1
Accessories		Optional Speaker Bracket: BBS251, BCS251, BWS251-300, BWS251-400
Crossover		2.1 kHz