



The CBR15 provides the lowest frequency in its lineup, delivering outstanding performance for the front-of-house sound for live performance, DJ events or for installation situations that require highly prominent low and high SPL.

Specifications

General specifications		
Speaker type		2-way Speaker, Bass-reflex Type
Frequency range (-10dB)		46 Hz - 20 kHz
Nominal coverage	H	90°
	V	60°
Components	LF	15" Cone, 2.5" Voice Coil (Ferrite Magnet)
	HF	1.4" Voice Coil, Compression Driver (Ferrite Magnet)
Power rating	NOISE	250W
	PGM	500W
	PEAK	1000W
Nominal impedance		8Ω
SPL	Sensitivity (1W; 1m on axis)	96dB SPL
	Peak (Calculated)	126 dB SPL
I/O connectors		1/4" Phone x 1, speakON NL4MP x 1
Dimensions	W	455mm (17.9")
	H	700mm (27.6")
	D	378mm (14.9")
Net weight		17.7 kg (39.0 lbs)
Cabinet material		Plastic
Finish		Black
Handle		Side x 2
Flying and mounting hardware		Bottom x 2, Rear x 1 (Fit for M8 x 15mm Eyebolts)
Pole socket		Φ35 mm Bottom x 1
Accessories		Optional Speaker Bracket: BBS251, BCS251, BWS251-300, BWS251-400
Crossover		2.0 kHz